

# ACRYLIC WALL PUTTY



## About

AMCOS PAINTS ACRYLIC WALL PUTTY is a water based putty for interior surfaces, which gives a strong and smooth finish. It is designed to achieve excellent filling and leveling of the surface imperfections and better sanding. The acrylic part associated with this formulation ensures great smoothness, better coverage and finish to the top coat.

## Features

◆ Good adhesion ◆ Good bonding with topcoats ◆ Good filling properties ◆ Good workability ◆ Excellent smooth finish

## Recommended surfaces

Concrete, cement plaster, masonry, brickwork & asbestos

## Surface preparation

Surface should be completely cured and free from dust, grease or loose particles. Any algal fungal growth should be properly removed and cleaned with bio wash to prevent the growth. Cracks should be properly sealed (Hairline cracks using AMCOS MASTER SEAL, cracks up to 2 mm using AMCOS SEAL AND FILL and cracks above 2 mm should be addressed by civil maintenance work).

## Recommended application method



Putty knife

## Points to note

- Mix well before use.
- Actual coverage may vary depending upon the method and conditions of application, surface conditions, application skill, surface roughness and porosity etc.
- Stability of thinned paint - 24 hours.
- Do not apply on damp and uncured walls directly. On mild damp wall and fresh walls it is highly recommended to apply one coat of AMCOS PLASTER SEALER.
- Hairline cracks can be filled by AMCOS MASTER SEAL. Cracks up to 2 mm can be filled by AMCOS SEAL AND FILL. Cracks above 2 mm should be addressed by civil work.
- Recoat period is quoted for 25°C and 50% relative humidity, these may vary under different conditions.
- Keep the container tightly closed after opening to prevent drying.
- Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

## Safety

- Wear masks, gloves, safety goggles and protective clothing while handling and application of paint.
- Keep out of reach of children and away from eatables.
- Store paints away from direct sunlight, heat open fire and water.
- Do not pour the leftover paints in drains. Dispose off the paint left overs and containers as per local regulations.
- Splashes on skin should be cleaned with a suitable solvent, washed off with soap and water.
- In case of any accidental ingestion or contact with eye, seek immediate medical attention.
- Lead content does not exceed 90 ppm.

Disclaimer: The information contained with this datasheet is based on our laboratory and practical experiments and we may change these with out notice. As the products are often used under conditions beyond our control, we do not take responsibility and liability for anything other than the quality of the product itself.

## Directions for use

Apply one coat of AMCOS PAINTS PLASTER SEALER or AMCOS PAINTS WALL PRIMER INTERIOR and allow to dry. Apply AMCOS PAINTS ACRYLIC WALL PUTTY as such using a putty knife. Dilute AMCOS PAINTS ACRYLIC WALL PUTTY with water if required. Allow to dry for 6-8 hours. Apply second coat of AMCOS PAINTS ACRYLIC WALL PUTTY if required. Allow to dry for 6-8 hours. Sand the applied surface using sand paper/emery paper and wipe clean. Apply one coat of AMCOS PAINTS PLASTER SEALER or AMCOS PAINTS WALL PRIMER INTERIOR and allow to dry. Apply 2-3 coats of the desired AMCOS PAINTS finish coat.

## Technical data

Dilution	: with clean and fresh water if required
Coverage	: 10-15 sq.ft./kg/coat
Surface dry	: 25 minutes
Hard dry	: 6 hours
Recoating interval	: 8 hours

## Packing



2kg

10kg

20kg

## Colour



◆ White