

WALL PRIMER EXTERIOR



About

AMCOS WALL PRIMER EXTERIOR is a water based wall coating for exterior applications as an undercoat to emulsions. It provides excellent opacity, excellent adhesion, better coverage and rich look to the topcoat emulsion. AMCOS WALL PRIMER EXTERIOR is resistant to chalking and thus provide better life to the topcoat.

Features

- ◆ Good adhesion ◆ Good hiding ◆ Good bonding with topcoats
- ◆ Good coverage

Recommended surfaces

Concrete, cement plaster & masonry

Surface preparation

Surface should be completely cured and free from dust, grease or loose particles. Any algal fungal growth should be properly removed and cleaned with bio wash to prevent the growth. Cracks should be properly sealed (Hairline cracks using AMCOS MASTER SEAL, cracks up to 2 mm using AMCOS SEAL AND FILL and cracks above 2 mm should be addressed by civil maintenance work). Ensure that the surface is prepared well before starting the application.

Recommended application method



Brush

Roller

Spray

Points to note

- Mix well before use.
- It is advisable to strain before application.
- Actual coverage may vary depending upon the method and conditions of application, surface conditions, application skill, surface roughness and porosity etc.
- Stability of thinned paint - 24 hours.
- Do not apply on damp and uncured walls directly. On mild damp wall and fresh walls it is highly recommended to apply one coat of AMCOS PLASTER SEALER.
- Hairline cracks can be filled by AMCOS MASTER SEAL. Cracks up to 2 mm can be filled by AMCOS SEAL AND FILL. Cracks above 2 mm should be addressed by civil work.
- Recoat period is quoted for 25°C and 50% relative humidity, these may vary under different conditions.
- It is advisable to check and maintain the diluted paints consistency in certain intervals based on atmospheric conditions to avoid application issues such as poor finish and less coverage due to solvent evaporation.
- Keep the container tightly closed after opening to prevent drying.
- Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Safety

- Wear masks, gloves, safety goggles and protective clothing while handling and application of paint.
- Keep out of reach of children and away from eatables.
- Store paints away from direct sunlight, heat open fire and water.
- Do not pour the leftover paints in drains. Dispose off the paint left overs and containers as per local regulations.
- Splashes on skin should be cleaned with a suitable solvent, washed off with soap and water.
- In case of any accidental ingestion or contact with eye, seek immediate medical attention.
- Lead content does not exceed 90 ppm.

Disclaimer: The information contained with this datasheet is based on our laboratory and practical experiments and we may change these with out notice. As the products are often used under conditions beyond our control, we do not take responsibility and liability for anything other than the quality of the product itself.

Directions for use

Mix well AMCOS WALL PRIMER EXTERIOR with water in recommended dilution ratio. Apply one coat and allow to dry for 4-6 hours. After complete drying, apply selected topcoat with recommended dilutions.

Technical data

Dilution	: 50% with clean and fresh water
Coverage	: 140-150 sq.ft./ltr/coat
Surface dry	: 45 minutes
Hard dry	: 6 hours
Recoating interval	: 12 hours

Packing



1L

4L

10L

20L

Colour



◆ White